

## The low-cost ATM for low-traffic locations.

The 8100 is our lowest cost ATM designed for merchants with low-traffic, tended locations who are over served by bigger, more expensive ATMs.

Our basic model, the 8100, will take up the least amount of floor space, yet provide all the customer convenience associated with having an ATM at your location. This smaller design makes the 8100 ideal for virtually any location, and turns extra floorspace into a profit center.

The 8100 includes the basic essentials for an ATM, making it easier for merchants to manage, all at the most cost-competitive price.

The 8100 features Triton's own TDM-50 dispensing mechanism, which requires the least amount of steps to handle. With features such as a top loading profile and a single cassette that slides in and out, the TDM-50 requires less time for the merchant to load.

Because it's from Triton, you can count on the 8100 delivering unparalleled reliability and quality. The 8100 incorporates state-of-the art electronics and a key-lock mechanism, most suitable for tended locations.

The 8100 features VISA Encrypting PIN Pad (VEPP) and Triple DES, the new standard for PIN encryption. Furthermore, the 8100 meets all ADA requirements.

Triton's cost-competitive 8100 is designed with low-cost and low-traffic locations in mind.



WHERE MONEY COMES FROM. ®

A 5 DOVER COMPANY



CORNERSTONE

PROCESSING SOLUTIONS

Credit Card & ATM Processing Services

1600 S. Main Street, Oshkosh, WI 54902

TEL: 888-878-2615 FAX: 866-345-9264

www.cornerstoneps.net



8100 with backlit topper



## The low-cost ATM for low-traffic locations.


## FEATURES:

- Available in Bayou Bronze
- Single cassette TDM-50
- 5.7" (145 mm) monochrome transaction screen
- 2" (51 mm) line thermal printer
- 58 mm paper (8100 paper can also be used in the 9100)
- 14.4k baud modem standard
- Key lock standard, dial and electronic lock optional
- Dip-style card reader (EMV optional)
- Small footprint
- Dimensions:
  - · 16" wide (405 mm)
- · 13" deep (330 mm)
- · 49" high (1245 mm) without topper
- · 60" high (1524 mm) with topper
- Non UL cabine
- Weight up to 107 lb (49 kg)

- Dial up communications standard, optional TCP/IP communications, optional wireless
- Audio transactions for the visually impaired
- VISA Encrypting PIN Pad (VEPP) to comply with international encryption standards and Triple DES compliant
- Backlit graphic topper option
- Triton Connect™ compatible
- Advertising revenue potential:
  - · Decal and signage
- · Couponing text
- · Transaction screen

## **OPERATING SPECS:**

- Temperature:
- · 10° to 30° C / 50° to 86° F
- · Relative humidity:
  - · 20% to 80% non-condensing
- Power consumption:
  - · 2.0A @ 115 VAC at 60 Hz
  - · 1.0A @ 230 VAC at 50 Hz



The dimensions shown comply with U.S. Federal ADA guidelines. For installation within the U.S., be sure to check state and local guidelines for complete compliance. For non-USA installations, check regulations for the country in which the machine will be installed.

\*specifications subject to change without notice

ATM INSTALLATION SPACE REQUIREMENTS FOR ADA COMPLIANCE

